# **Fleximax**

#### **DESCRIPTION**

- · Industrial protective glove.
- Elastomer (nitrile) coating on a textile liner.
- 3 lengths available:
  - 270 mm (10.5 in) protection of the wrist,
  - 350 mm (14 in) protection of forearm,
  - 400 mm (18 in) protection of the forearm,
- 4 sizes available: 7, 8, 9 and 10 (27 version).
- 3 sizes available: 8, 9 and 10 (35 and 40 version).
- Trade unit: 10 pairs, 100 pairs in a transit case (version 35 and 40) and 150 pairs in a transit case (version 27).

#### **CHARACTERISTICS**

- · Fine gauge 100% cotton interlock knitted liner.
- · Assembly of the two parts by chain stitch.
- Full dinaprene elastomer coating, a mix of several carboxylated nitrile rubbers formulated to enhance resistance to chemical and mechanical aggression.

### **PERFORMANCES**

- · High flexibility and excellent dexterity.
- · Excellent resistance to abrasion and small cuts.
- Antistatic properties offer hand protection against electrostatic discharge.
- Good chemical resistance to solvents, acids, bases, oils, greases, petrol and alcohol.
- In compliance with the standards EN420 (General requirements), EN388 (Mechanical Hazards) and EN 374 (Chemicals and micro-biologicalhazards) by the notified laboratory IFTH - Institut Français Textile-Habillement.
- Manufactured under EC quality assurance system carried out by the BSI body.

## **APPLICATIONS**

- CE Complex Design.
- · For handling aggressive products.
- For assembly and machining work involving contact with chemical products (immersion and splash).
- · For general industrial maintenance activities.





3121



EN 420

5 Dexterity

EN 388

3 Abrasion

1 Cut 2 Tear

1 Puncture

EN 374

3 J - N-heptane

6 K - Caustic soda solution 40 %

2 L - Sulfuric acid 96 %



EN 388

Mechanical hazards

EN 374

Chemical hazards

EN 374 Microbiogical hazards

#### Order codes

Sizes
Fleximax 27
Fleximax 35
Fleximax 40

**7 (S)** 1950E11000 8 (M) 1950E12000 1970E12000 09999388 9 (L) 1950E13000 1970E13000 09999389

10 (XL) 1950E14000 1970E14000 09999390



N° CMS/TDS/FleximaxEN/FT/11 - 09/09





